GTA Containers, Inc. 4201 Linden Ave., South Bend, IN 46619.

Hardware & Accessories

Tanks are supplied completely ready for use.

Each tank is supplied with aluminum fittings which are permanently bonded to the tank, as follows:

| Bonded Fittings | 3K | 10K | 20K | 50K | 210K |
|--------------------------------|----|-----|-----|-----|------|
| Filler/discharge assembly 4 in | 2 | 2 | 2 | 2 | |
| Filler/discharge assembly 6 in | | | | | 2 |
| Vent Fitting Assembly, 2 in | 1 | 1 | 1 | 1 | 1 |
| Drain Fitting Assembly, 2 in | 2 | 2 | 2 | 2 | 4 |

Packed with the tank are the following quick disconnect fittings and accessories:

| Quick Disconnect Fittings & Accessories | Quantity per tank | | | | |
|--|-------------------|-----|-----|-----|------|
| | 3K | 10K | 20K | 50K | 210K |
| Drain Hose, M X F, 2 in x 8 ft | 2 | 2 | 2 | 2 | 4 |
| Drain Valve Assembly, M X F, 2 in | 2 | 2 | 2 | 2 | 4 |
| Filler/Discharge Hose Assembly, M X F, 4 in x 10 ft | 1 | 1 | 1 | 1 | |
| Filler/Discharge Valve Assembly, M X F, 4 in | 1 | 1 | 1 | 1 | |
| Filler/Discharge Hose Assembly, M X F, 6 in x 10 ft | | | | | 2 |
| Filler/Discharge Valve Assembly, M X F, 6 in | | | | | 2 |
| Repair Kit, ATPD-2263, Type II | 1 | 1 | | | |
| Repair Kit, ATPD-2263, Type III | | | 1 | 1 | 1 |
| Set of Replacement O-Rings, Gaskets and Fasteners | | | | | 1 |
| 90 Degree Elbow, M X F, 4 in | 1 | 1 | 1 | 1 | |
| 90 Degree Elbow, F X F, 4 in | 1 | 1 | 1 | 1 | |
| 90 Degree Elbow, M X F, 6 in | | | | | 1 |
| 90 Degree Elbow, F X F, 6 in | | | | | 1 |
| Flame Arrestor with Pressure Relief Cap, 2 in (fuel tanks) | 1 | 1 | 1 | 1 | 1 |
| Pressure Relief Cap (Mushroom Type), 2 in (water tanks) | 1 | 1 | 1 | 1 | 1 |

Berm Liners & Ground Cloths

Berm liners and ground cloths for secondary containment are available for deployment with fuel tanks and water tanks, respectively. Sizes are as follows:

| Description | For use with tank capacity | Ground Cloth Dimensions | Berm Liner Dimensions |
|-------------|----------------------------|----------------------------|--------------------------|
| Size I | 3,000 gallons | 16 ft x 16 ft | 37 ft x 37 ft |
| Size II | 10,000 gallons | 25 ft x 25 ft | 52.5 ft x 52.5 ft |
| Size III | 20,000 gallons | 30 ft x 30 ft | 59 ft x 59 ft |
| Size IV | 50,000 gallons | 68 ft x 28 ft | 100 ft x 60 ft |
| Size V | 210,000 gallons | 70 ft x 70 ft | 108 ft x 108 ft |

| Capacity | DIMENSIONS, | DIMENSIONS, CRATE | TANK | CRATED |
|-----------------|---------------|------------------------------|--------------|-----------|
| U.S. Gallons | UNFOLDED | | WEIGHT, | WEIGHT |
| | | | EMPTY | |
| 3,000 gallons | 14 ft x 14 ft | 85 in x 60 in x 31.5 in | 346 lbs | 634 lbs |
| 10,000 gallons | 22 ft x 22 ft | 85 in x 60 in x 31.5 in | 533 lbs | 857 lbs |
| 20,000 gallons | 24 ft x 28 ft | 85 in x 60 in x 31.5 in | 656 lbs | 910 lbs |
| 50,000 gallons | 25 ft x 65 ft | 96 in x 60 in x 31.75 in | 1,255 lbs | 1,806 lbs |
| 210,000 gallons | 70 ft x 70 ft | 114.25 in x 80 in x 43.75 in | 5,000 lbs | 5,700 lbs |